



- NOTES:
1. UNLESS OTHERWISE INDICATED, RESISTOR VALUES ARE IN OHMS, CAPACITOR VALUES ARE IN PICOFARADS, INDUCTOR VALUES ARE IN MICROHENRIES.
 2. NON-POLARIZED CAPACITORS ARE CHIP-TANTALUM TYPE UNLESS OTHERWISE INDICATED.
 3. POLARIZED CAPACITORS ARE CHIP-TANTALUM TYPE UNLESS OTHERWISE INDICATED.
 4. "NLT" MEANS COMPONENT IS NOT USED.
 5. DC VOLTAGES ARE MEASURED WITH A HIGH IMPEDANCE (10 MEGOHM) DC VOLTMETER.
 6. AC VOLTAGES ARE MEASURED WITH A HIGH IMPEDANCE AC RMS VOLTMETER.
 7. ALL VOLTAGE MEASUREMENTS ARE IN THE RECEIVE MODE UNLESS INDICATED AS FOLLOWS:
(R) RECEIVE MODE
(T) TRANSMIT MODE
 8. MEASURED IN THE RECEIVE MODE WITH AN ON-CHANNEL UNMODULATED SIGNAL AT A LEVEL OF -20 DBM.
 9. MEASURED IN THE RECEIVE MODE WITH AN ON-CHANNEL SIGNAL AT A LEVEL OF -20 DBM, MODULATED WITH 1 KHZ AT 3 KHZ DEVIATION (FOR 20/25 KHZ MODELS) OR 1.5 KHZ DEVIATION (FOR 12.5 KHZ MODELS), MEASURED WITH AN AC RMS VOLTMETER.
 10. SAME AS NOTE 8 EXCEPT WITH VOLUME CONTROL ADJUSTED FOR 500 MILLIVOLTS (2.82 VOLTS RMS ACROSS 16-OHM LOAD CONNECTED TO THE EXT SPKR JACK).
 11. MEASURED IN THE TRANSMIT MODE WITH A 1 KHZ, 11 MV RMS SIGNAL APPLIED TO THE EXTERNAL MICROPHONE INPUT.

